



EFIXR angle brackets are intended for all assemblies for the design and installation of interior and exterior joinery. EFIXR stiffener improves rigidity particularly for large models.

FEATURES






Material

- Galvanized steel S250GD + Z275 according to NF EN 10346.

Benefits

- The 2 obround holes make adjustments easier.



APPLICATIONS

Header member



- Supporting member type:** wood, concrete, metal, PVC.
- Supported member type:** wood, concrete, metal, PVC.

For Use With

- Frames.
- Storage cabinets.

TECHNICAL DATA

Dimensions and drill holes



EFIXR553C50

EFIXR753C50

INSTALLATION

Fixing

Nail holes dia. 5 mm and obround holes width 8.5 and 6.5 mm.

On wood:

- CNA annular ring-shank nails 4.0 mm.
- Bolts.
- LAG screws.
- CSA screws dia. 5.0 mm.

On concrete:

- HIPC 8-60/20 drive anchors.

On metal:

- Bolts.
- Self-drilling screws.

Installation

1. Approcher l'élément à fixer du support,
2. Pointer l'élément. Celui-ci peut aussi être vissé à l'aide de vis adaptées,
3. Si le support est en bois, l'équerre est aussi pointée ou vissée sur celui-ci,
4. Si le support est en béton, fixer l'équerre en respectant les préconisations de pose de l'ancrage choisi.

