

Declaration of Performance

In accordance with the CPR Regulation (EU) N° 305/2011

Soudal Acryrub

Revision: 30/04/2014

Page 1 from 3

Reference nr DOP: 230681

Unique identification code of the product type:

Soudal Acryrub

Intended use or uses of the construction product:

Sealant for facade for interior and exterior application.

Construction product in accordance with applicable harmonised specifications:

EN 15651-1:2012: Type F - EXT-INT: CLASS 12.5P

System or systems of assessment and verification of consistency of performance of the construction product, as set out in Annex V:

System 3

System 3: for reaction to fire

Name and contact address of the manufacturer as required pursuant to Article 11(5):

Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium

The notified body:

GINGER CEBTP, NB 0074 has carried out Determination of Product Type under system 3.

Declaration of Performance

In accordance with the CPR Regulation (EU) N° 305/2011

Soudal Acryrub

Revision: 30/04/2014

Page 2 from 3

Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	Class E	EN 15651-1: 2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	≤ 25%	
Elastic recovery	< 40%	
Adhesion/cohesion at maintained extension after water immersion	NF	
Elongation at break	≥ 100%	
Tensile properties at break after water immersion	≥ 100%	
Durability	Pass	

Conditioning:

Method A

Substrate:

Aluminium

Mortar

The performance of this product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for on behalf of the manufacturer by



Eric van Spreuwel

Technical Product Manager
BE-2300 Turnhout, 30/04/2014

CE marking

In accordance with the CPR Regulation (EU) N° 305/2011

Revision: 30/04/2014

Page 3 from 3



NB 0074

Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium

14

Reference nr DOP: 230681

EN 15651-1: 2012

Sealant for facade for interior and exterior application.

Soudal Acryrub

EN 15651-1:2012: Type F - EXT-INT: CLASS 12.5P

Conditioning:

Method A

Substrate:

Aluminium

Mortar

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	Class E	EN 15651-1: 2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	≤ 25%	
Elastic recovery	< 40%	
Adhesion/cohesion at maintained extension after water immersion	NF	
Elongation at break	≥ 100%	
Tensile properties at break after water immersion	≥ 100%	
Durability	Pass	