

## Declaration of Performance

In accordance with the CPR Regulation (EU) N° 305/2011

---

### Soudal Fix All Turbo

---

Revision: 22/07/2014

Page 1 from 3

Reference nr DOP: 230211

Unique identification code of the product type:

**Soudal Fix All Turbo**

Intended use or uses of the construction product:

**Sealant for facade for interior application.**

Construction product in accordance with applicable harmonised specifications:

**EN 15651-1:2012: Type F -INT**

System or systems of assesment and verification of consistency of performance of the construction product, as set out in Annex V:

**System 4**

**System 3: for reaction to fire**

Name and contact address of the manufacturer as required pursuant to Article 11(5):

**Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium**

The notified body:

**WFR GENT, NB 1173 has carried out Determination of the Product Type under system 3 for reaction to fire.**

## Declaration of Performance

In accordance with the CPR Regulation (EU) N° 305/2011

---

### Soudal Fix All Turbo

---

Revision: 22/07/2014

Page 2 from 3

#### Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	Class E	EN 15651-1: 2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	≤ 45%	
Elongation at break	≥ 25%	
Durability	Pass	

#### Conditioning:

Method B

#### Substrate:

Aluminium  
Mortar

The performance of this product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for on behalf of the manufacturer by



Ing. W. Dierckx

Technical Product Manager  
BE-2300 Turnhout, 22/07/2014

## CE marking

In accordance with the CPR Regulation (EU) N° 305/2011

Revision: 22/07/2014

Page 3 from 3



NB 1173

**Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium**

14

Reference nr DOP: 230211

EN 15651-1: 2012

Sealant for facade for interior application.

### **Soudal Fix All Turbo**

EN 15651-1:2012: Type F -INT

**Conditioning:**

Method B

**Substrate:**

Aluminium

Mortar

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	Class E	EN 15651-1: 2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	≤ 45%	
Elongation at break	≥ 25%	
Durability	Pass	