

TYGRIS TECHNICAL DATA SHEET

Precision Aerosols

W D Power Anti-Rust Fluid

CODE: **IS3**

Extra high performance de-watering and anti-rust agent

A professional very high performance water displacement spray. So effective that it will actually displace other leading brands, IS3 also offers good lubrication characteristics. A protective film is left on the treated surface, guarding against corrosion. Use on tooling, chains, switchgear, machinery and ignition systems.



Benefits:

- Excellent water displacement – chases away droplets
- Can be applied to wet surfaces
- Removes moisture from ignition systems for easier starting
- Fast drying
- Virtually transparent coating – removal not normally necessary
- Protects against rust for up to 2 years inside storage
- Acts as a light lubricant
- The dry coating meets MOD specification 68-19 (PX-24) and NATO Code C-634

Technical Data:

Appearance: Pale amber thin free flowing liquid
Odour: Light solvent odour
Contents: A blend of moisture displacing additives, corrosion inhibitors and wetting agents in naphtha and hydrocarbon propellants

Storage: Below 50°C
Flash Point: <0°C
Temperature range:
Relative Gravity: 0.797
Pack Sizes: 12 x 400ml cans
Directions for Use: Shake can before use. Spray lightly from a distance of 20-30cm. For hard to reach places use applicator tube provided. Not recommended for use on plastics.