

### Description

High temperature anti-seize protection

A high temperature lubricant providing outstanding overall metal protection against heat, rust, seizure and corrosion. Resistance to water and acids is high and it will not burn off under extreme stress. For use on threaded components, pins, valve stems in a range of materials including austenitic stainless steel. Used on brake callipers and the back of brake pads it will help eliminate brake squeal.



### Outstanding Features

- Effective up to 1100°C
- Water and acid resistant
- Use on a wide range of metals
- Prevents seizure of threaded parts
- Will not burn or wash off
- Eliminates brake squeal
- Assists in assembly and disassembly of components

### Directions for Use

Shake can well before use. Spray component from a distance of 15 to 30cm. Wipe off excess.  
**Do not apply to friction materials and pads.**

### Technical Data

|                   |   |
|-------------------|---|
| Appearance        | Soft copper coloured grease   |
| Odour             | Oily solvent  |
| Contents          | Blend of copper paste, calcium grease, mineral oils, and hydrocarbon propellants. No lead, silicone or chlorinated solvents |
| Storage           | Below 50°C  |
| Flash Point       | -60°C   |
| Temperature range | -150°C to 1100°C  |
| Relative Density  |   |
| Solubility        | Insoluble in water  |
| Pack Sizes        | 12 x 400ml cans   |

The content of this data sheet is given in good faith but without warranty.