



Nail plates can be used in various applications, in particular for jointing or the connection of wood elements in the same plan.



[UK-DoP-h10/0005](#)

## FEATURES




### Material

- Pre-galvanised mild steel.

### Benefits

- Versatility of Applications
- Can be bent on site



## APPLICATIONS

### Header member


- **Supporting member:** solid wood, glued-laminated wood, composite lumber, etc.
- **Supported member:** solid wood, glued-laminated wood, composite lumber, triangular trusses, profiles.

### For Use With

- Post/beam connection.
- Jointing.
- Repairs.
- Assemblies requiring a special bending on site, etc.

TECHNICAL DATA

NP Nail Plates



References	Dimensions [mm]			Holes
	A	B	Thickness	Diameter
NP40/120	40	120	1.5	Ø 4
NP80/140	80	140	1.5	Ø 4
NP80/180	80	180	1.5	Ø 4
NP80/200	80	200	1.5	Ø 4
NP80/220	80	220	1.5	Ø 4
NP80/260	80	260	1.5	Ø 4
NP100/140	100	140	1.5	Ø 4
NP100/200	100	200	1.5	Ø 4
NP100/240	100	240	1.5	Ø 4
NP100/300	100	300	1.5	Ø 4
NP140/180	140	180	1.5	Ø 4
NP140/200	140	200	1.5	Ø 4
NP140/260	140	260	1.5	Ø 4
NP160/340	160	340	1.5	Ø 4
NP200/260	200	260	1.5	Ø 4
NP220/300	220	300	1.5	Ø 4

## INSTALLATION

### Fixing


- 3.75x30mm Square Twist Nails.



Three way  
timber  
connection  
using NP.



Attaching wood  
rafters and  
square butting  
rafters.



T Connection  
using NP.

## TECHNICAL NOTES