



# SAFETY DATA SHEET

## FILL & FIX B1 GUN GRADE PU EXPANDING FOAM 750ml

SDS Ref:  
25  
Revision 1  
Revision Date:  
30.04.2019

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name FILL & FIX B1 GUN GRADE PU EXPANDING FOAM 750ml  
Product No. 247760

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Filling of gaps in interior applications and cavities. For filling and insulation around window frames and doors.

#### 1.3. Details of the supplier of the safety data sheet

Supplier T.I. Midwood & Co. Ltd  
TIMco House  
Green Lane  
Wardle  
Nantwich  
CW5 6BJ  
01829 261111

#### 1.4. Emergency telephone number

Tel: 01829 261111 (Office Hours Only)

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC 1272/2008)

GHS02 flame



Flam. Aerosol 1

H222-H229

Extremely flammable aerosol. Pressurised container:  
May burst if heated.



GHS08 health hazard

Resp. Sens. 1

H334

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carc. 2

H351

Suspected of causing cancer.

STOT RE 2

H373

May cause damage to organs through prolonged or repeated exposure.



GHS07

Acute Tox. 4

H332

Harmful if inhaled.

Skin Irrit. 2

H315

Causes skin irritation.

Eye Irrit. 2

H319

Causes serious eye irritation.

Skin Sens. 1

H317

May cause an allergic skin reaction.

STOT SE 3

H335

May cause respiratory irritation.

#### 2.2. Label elements

Label In Accordance With (EC) No. 1272/2008

The product is classified and labelled according to the CLP regulation.

# SAFETY DATA SHEET - FILL & FIX B1 GUN GRADE PU EXPANDING FOAM 750ml

Hazard pictograms



GHS02

GHS07

GHS08

Signal word

Danger

Hazard-determining components of labelling:  
diphenylmethanediisocyanate, isomers and homologues  
chlorinated paraffins, C14-17

Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H332	Harmful if inhaled.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
H351	Suspected of causing cancer.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P102	Keep out of reach of children.
P260	Do not breathe gas.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

## Additional information:

Persons already sensitised to diisocyanates may develop allergic reactions when using this product.  
Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.  
This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.  
Do not pierce or burn, even after use.  
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
Do not spray on an open flame or other ignition source.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
EUH204 Contains isocyanates. May produce an allergic reaction.

## 2.3. Other hazards

Results of PBT and vPvB assessment









PBT: Not applicable.  
vPvB: Not applicable.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Chemical characterisation: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

# SAFETY DATA SHEET - FILL & FIX B1 GUN GRADE PU EXPANDING FOAM 750ml

Dangerous components:		
CAS: 9016-87-9 EC number: 618-498-9	diphenylmethanediisocyanate, isomers and homologues  Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373;  Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	30 - 60%
CAS: 1244733-77-4 EC number: 911-815-4 Reg.nr.: 01-2119486772-26-xxxx	tris(2-chlorisopropyl)-phosphate  Acute Tox. 4, H302	< 25%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane  Flam. Gas 1, H220; Press. Gas C, H280	< 15%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-21194869440-21-xxxx	propane  Flam. Gas 1, H220; Press. Gas C, H280	< 15%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-31-xxxx	butane  Flam. Gas 1, H220; Press. Gas C, H280	< 15%
CAS: 86675-46-9 Reg.nr.: 01-2119972940-30-xxxx	halogenated polyetherpolyol  Acute Tox. 4, H30	< 15%
CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37-0001	dimethyl ether  Flam. Gas 1, H220; Press. Gas C, H280	< 10%

Additional information: For the wording of the listed risk phrases refer to section 16.

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

After skin contact:

Remove uncured foam using a piece of cloth and an unaggressive solvent, e.g. ethanol. Wash your hands and the cleaned skin surface using soapy water. Cured foam can be removed mechanically with the use of a brush, soap and plenty of water. Use protective cream after skin surface has been cleaned.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Do not induce vomiting; call for medical help immediately.

Rinse out mouth and then drink plenty of water.

### 4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

### 4.3. Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## SECTION 5: FIREFIGHTING MEASURES

### 5.1. Extinguishing media

Carbon dioxide.

Fire-extinguishing powder.

Foam.

Water spray.

Use fire extinguishing methods suitable to surrounding conditions.

For safety reasons unsuitable extinguishing agents: Water with full jet.

### 5.2. Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

# SAFETY DATA SHEET - FILL & FIX B1 GUN GRADE PU EXPANDING FOAM 750ml

## 5.3. Advice for firefighters

Cool endangered receptacles with water spray.

### Additional information:

Protective equipment:

Wear fully protective suit.

Wear self-contained respiratory protective device.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

---

### 6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

Wear protective clothing.

Do not breathe gas / fumes / vapour / spray.

Ensure adequate ventilation.

Wear protective equipment. Keep unprotected persons away.

### 6.2 Environmental precautions:

Do not allow to enter sewers / surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

### 6.3 Methods and material for containment and cleaning up:

Uncured foam adheres easily, hence it should be removed with caution. Remove instantly using a piece of cloth and solvents, e.g. acetone, alcohol. Remove cured foam mechanically.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

### 6.4 Reference to other sections

See Section 13 for disposal information.

## SECTION 7: HANDLING AND STORAGE

---

### 7.1 Precautions for safe handling

Ensure good ventilation / exhaustion at the workplace.

Open and handle receptacle with care.

Do not pierce or burn even after use. Use only as directed on the label.

Do not mix with any other chemical products.

Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

### 7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

This product is subject to regulations governing the storage of highly flammable aerosol products.

Storage rooms should be equipped with heat and smoke detectors.

Electrical equipment should be explosion-proof.

Information about storage in one common storage facility:

Do not store together with acids.

Do not store together with alkalis (caustic solutions).

Store away from oxidising agents.

Store away from foodstuffs.

Store away from plastic, rubber, aluminum, light-metals.

Further information about storage conditions:

Store in vertical position in closed original containers.

Store receptacle in a well ventilated area.

Protect from frost.

Store at temperature from +5°C to +30°C.

Store under lock and key and out of the reach of children.

Keep container tightly sealed.

Protect from heat and direct sunlight.

# SAFETY DATA SHEET - FILL & FIX B1 GUN GRADE PU EXPANDING FOAM 750ml

## 7.3. Specific end use(s)

No further relevant information available.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Additional information about design of technical facilities: No further data; see item 7.

### 8.1. Control parameters

Ingredients with limit values that require monitoring at the workplace:

CAS: 9016-87-9 DIPHENYLMETHANEDIISOCYANATE, ISOMERS AND HOMOLOGUES	
WEL	Short-term value: 0.07 mg/m <sup>3</sup> Long-term value: 0.02 mg/m <sup>3</sup> Sen; as -NCO
CAS: 115-10-6 DIMETHYL ETHER	
WEL	Short-term value: 958 mg/m <sup>3</sup> , 500 ppm Long-term value: 766 mg/m <sup>3</sup> , 400 ppm
CAS: 106-97-8 BUTANE	
WEL	Short-term value: 1810 mg/m <sup>3</sup> , 750 ppm Long-term value: 1450 mg/m <sup>3</sup> , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

#### DNELs

CAS: 9016-87-9 DIPHENYLMETHANEDIISOCYANATE, ISOMERS AND HOMOLOGUES		
Oral	DNEL	20 mg/kg/day (General population, consumers)
Dermal	DNEL	0.05 mg/kg/day (General population, consumers)
Inhalative	DNEL	0.05 mg/m <sup>3</sup> (General population, consumers) 0.05 mg/m <sup>3</sup> (Workers)
CAS: 115-10-6 DIMETHYL ETHER		
Inhalative	DNEL	471 mg/m <sup>3</sup> (General population, consumers) 1,894 mg/m <sup>3</sup> (Workers)
CAS: 86675-46-9 HALOGENATED POLYETHERPOLYOL		
Oral	DNEL	0.44 mg/kg/day (General population, consumers)
Dermal	DNEL	0.44 mg/kg/day (General population, consumers) 0.87 mg/kg/day (Workers)
Inhalative	DNEL	1.5 mg/m <sup>3</sup> (General population, consumers) 6 mg/m <sup>3</sup> (Workers)
CAS: 1244733-77-4 TRIS(2-CHLORISOPROPYL)-PHOSPHATE		
Oral	DNEL	0.52 mg/kg/day (General population, consumers) 1.04 mg/kg/day (Workers)
Dermal	DNEL	4 mg/kg/day (General population, consumers) 2.08 mg/kg/day (Workers)
Inhalative	DNEL	11.2 mg/m <sup>3</sup> (General population, consumers) 5.82 mg/m <sup>3</sup> (Workers)

#### PNECs

CAS: 9016-87-9 DIPHENYLMETHANEDIISOCYANATE, ISOMERS AND HOMOLOGUES	
(freshwater)	1 mg/l
(sea water)	0.1 mg/l
(soil)	1 mg/kg
CAS: 86675-46-9 HALOGENATED POLYETHERPOLYOL	
(freshwater)	1 mg/l
(sea water)	0.1 mg/l
(freshwater sediments)	37.5 mg/kg
(sea water sediments)	3.75 mg/kg
(soil)	6.92 mg/kg

## SAFETY DATA SHEET - FILL & FIX B1 GUN GRADE PU EXPANDING FOAM 750ml

CAS: 115-10-6 DIMETHYL ETHER	
(freshwater)	0.155 mg/l
(sea water)	0.016 mg/l
(freshwater sediments)	0.681 mg/kg
(sea water sediments)	0.069 mg/kg
(soil)	0.045 mg/kg

CAS: 1244733-77-4 TRIS(2-CHLORISOPROPYL)-PHOSPHATE	
(freshwater sediments)	13.4 mg/kg
(sea water sediments)	1.34 mg/kg
(soil)	1.7 mg/kg

### 8.2. Exposure controls

Protective equipment

General protective and hygienic measures:

Do not inhale gases / fumes / aerosols.  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

EN 374

The glove material has to be impermeable and resistant to the product / the substance / the preparation.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

Material of gloves

Polyethylene gloves.

Recommended thickness of the material:  $\geq 0.020$  mm.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

Short-term exposure  $\geq 10$  min (EN 374)

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.



Tightly sealed goggles

EN 166

Body protection: Protective work clothing.

# SAFETY DATA SHEET - FILL & FIX B1 GUN GRADE PU EXPANDING FOAM 750ml

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

---

### 9.1. Information on basic physical and chemical properties

General Information

Appearance:

Form:

Aerosol

Rapidly curing foam dispensed by gaseous propellant from an aerosol container

Different according to colouring

Odour:

Colour:  
Characteristic

pH-value:

-

Change in condition

Melting point/freezing point:

Not determined

Initial boiling point and boiling range:

Not applicable, as aerosol

Flash point:

<0 °C  
(propellant)

Auto-ignition temperature:

> +350 °C (propellant)

Explosive properties:

Heating may cause an explosion.

Explosion limits:

Lower:

+/- 1.5 Vol %

Upper:

+/- 11.0 Vol %

Vapour pressure:

>500 kPa (in the container)  
< 1\*10<sup>-5</sup> mmHg w 25°C (MDI)

Density at 20 °C:

≤1.3 (PMDI) g/cm<sup>3</sup>

Solubility in / Miscibility with water:

Insoluble  
Reacts with water

Partition coefficient: n-octanol/water:

Not determined

### 9.2. Other information

No further relevant information available.

## SECTION 10: STABILITY AND REACTIVITY

---

### 10.1 Reactivity

No further relevant information available.

### 10.2. Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known.

### 10.4. Conditions to avoid

No further relevant information available.

### 10.5. Incompatible materials

Strongly reacts with water and other substances containing an active hydrogen atom.

### 10.6. Hazardous decomposition products

No dangerous decomposition products known.

## SECTION 11: TOXICOLOGICAL INFORMATION

---

### 11.1. Information on toxicological effects

Acute toxicity

Harmful if inhaled.

LD/LC50 values relevant for classification:

# SAFETY DATA SHEET - FILL & FIX B1 GUN GRADE PU EXPANDING FOAM 750ml

CAS: 9016-87-9 DIPHENYLMETHANEDIISOCYANATE, ISOMERS AND HOMOLOGUES		
Oral	LD50	>10,000 mg/kg (rat) (OECD401)
Dermal	LD50	>9,400 mg/kg (rabbit) (OECD402)

CAS: 1244733-77-4 TRIS(2-CHLORISOPROPYL)-PHOSPHATE		
Oral	LD50	1,017 mg/kg (rat)
Dermal	LC50	>2,000 mg/kg (rat)

Primary irritant effect: Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/irritation	Causes serious eye irritation.
Respiratory or skin sensitisation	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.
Germ cell mutagenicity	Based on available data, the classification criteria are not met.
Carcinogenicity	Suspected of causing cancer.
Reproductive toxicity	Based on available data, the classification criteria are not met.
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	Based on available data, the classification criteria are not met.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

Aquatic toxicity:

CAS: 1244733-77-4 TRIS(2-CHLORISOPROPYL)-PHOSPHATE	
EC50	47 mg/l (algae)

### 12.2. Persistence and degradability

Not biodegradable.

### 12.3. Bioaccumulative potential

Does not accumulate in organisms.

### 12.4. Mobility in soil

No further relevant information available.

Additional ecological information:

General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

### 12.5. Results of PBT and vPvB assessment

PBT: Not applicable.  
vPvB: Not applicable.

### 12.6. Other adverse effects

No further relevant information available.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Do not allow to enter surface or ground water.

Dispose of in a safe manner in accordance with local / national regulations.

Assigning a code from the waste catalogue depends on the sector, in which the user operates, as well as on arrangements made between the waste generator and a competent environment protection department.

Substance/mixture as a waste compound brings hazardous properties HP: 3, 4, 5, 6, 7, 13



# SAFETY DATA SHEET - FILL & FIX B1 GUN GRADE PU EXPANDING FOAM 750ml

## 13.2 European waste catalogue

15 01 11\* metallic packaging containing a hazardous solid porous matrix (for example asbestos), including empty pressure containers

Uncleaned packaging:  
Recommendation: Disposal must be made according to official regulations.

## SECTION 14: TRANSPORT INFORMATION

### 14.1. UN number

ADR, IMDG, IATA UN1950

### 14.2. UN proper shipping name

ADR, IMDG, IATA AEROSOLS

### 14.3. Transport hazard class(es)

ADR



Class 2 5F Gases  
Label 2.1  
IMDG, IATA



Class 2.1  
Label 2.1

### 14.5. Environmental hazards

Marine pollutant: No.

### 14.6. Special precautions for user

Warning: Gases.  
Danger code (Kemler): -  
EMS Number: F-D,S-U

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

### Transport/Additional information:

ADR  
Limited quantities (LQ) 1L  
Excepted quantities (EQ) E0  
Transport category 2  
Remarks: Exemption from ADR provisions by LQ principal (rule 3.4)  
- Inner packaging, max. 1 liter in capacity; outer packaging – max. gross weight of 30kg.  
- Inner packaging, max. 1 liter in capacity, based on common ground and covered with shrink film – max. gross weight of 20kg.  
Tunnel restriction code: D.

UN "Model Regulation": UN 1950 AEROSOLS, 2.1

## SECTION 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances

- ANNEX I None of the ingredients is listed.

Seveso category P3a FLAMMABLE AEROSOLS

Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t  
REGULATION (EC) No 1907/2006

# SAFETY DATA SHEET - FILL & FIX B1 GUN GRADE PU EXPANDING FOAM 750ml

ANNEX XVII Conditions of restriction: 56

## Other regulations, limitations and prohibitive regulations

Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

## 15.2. Chemical Safety Assessment

A Chemical Safety Assessment has not been carried out.

## SECTION 16: OTHER INFORMATION

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

H220	Extremely flammable gas.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.

The information stated above is based on current knowledge and applies to the product in the form in which it is used. Data concerning this product is presented in order to fulfill safety requirements and not to guarantee its specific properties.

In cases when application conditions are not subject to manufacturer's control, the responsibility for safe product use and obeying law regulations in particular, lies on the user's side.

Information in the appropriate technical data sheet of product.

## Abbreviations and acronyms:

ADR:	Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG:	International Maritime Code for Dangerous Goods
IATA:	International Air Transport Association
GHS:	Globally Harmonised System of Classification and Labelling of Chemicals
EINECS:	European Inventory of Existing Commercial Chemical Substances
ELINCS:	European List of Notified Chemical Substances
CAS:	Chemical Abstracts Service (division of the American Chemical Society)
DNEL:	Derived No-Effect Level (REACH)
PNEC:	Predicted No-Effect Concentration (REACH)
LC50:	Lethal concentration, 50 percent
LD50:	Lethal dose, 50 percent
PBT:	Persistent, Bioaccumulative and Toxic
SVHC:	Substances of Very High Concern
vPvB:	very Persistent and very Bioaccumulative
Flam. Gas 1:	Flammable gases – Category 1
Aerosol 1:	Aerosols – Category 1
Press. Gas (Comp.):	Gases under pressure – Compressed gas
Acute Tox. 4:	Acute toxicity – Category 4
Skin Irrit. 2:	Skin corrosion/irritation – Category 2
Eye Irrit. 2:	Serious eye damage/eye irritation – Category 2
Resp. Sens. 1:	Respiratory sensitisation – Category 1
Skin Sens. 1:	Skin sensitisation – Category 1
Carc. 2:	Carcinogenicity – Category 2
STOT SE 3:	Specific target organ toxicity (single exposure) – Category 3
STOT RE 2:	Specific target organ toxicity (repeated exposure) – Category 2